

B23 113-100

Namn: **Elmätare B23**
3-fas, direktmätare 65A 230/400VAC, MID, M-bus

Typ: B23 113-100
EAN: 7392696001656
E-nr: 0900038



Beskrivning: Elmätare för fördelnings/undermätning. B23 113-100 har instrumentvärden och möjlighet att läsa dessa på display eller fjärravläsa dem via M-bus. Samtliga EQ mätare i B-serien är MID godkända och ges i klass B eller C (klass 1 eller 0,5S enl. IEC). Perfekt för integrering i ett system tillsammans med exempelvis flödesmätare.

Förpackning: 1
Enhet: st

ETIM

ETIM 7 EC001506 (EC001506)

ETIM 7

| | |
|-----------------------------|---------------------------------|
| Type of meter | Electronic |
| Nominal current (In) | 5 A |
| Max. current (Imax) | 65 A |
| Nominal voltage (Un) N-L | 176 ... 276 V |
| Nominal voltage (Un) L-L | 400 V |
| Frequency | 47.5 ... 63 Hz |
| Accuracy class | B |
| Pole type | Four conductor |
| Model | Direct measurement |
| Energy type | Effective power |
| Suitable for | Purchase |
| Tariff type | One-tariff |
| Measuring type load profile | 1 |
| Escapement mechanism | 1 |
| Calibrated | 1 |
| Approval | Measuring Instruments Directive |
| Pulse output | Electrical |
| Pulse type | S0 |
| Pulse rate | 1 ... 9999 Imp/kWh (kvarh) |
| Type of indication | Digital |
| Mounting method | DRA (DIN-rail adapter) |



PRODUKTBLAD

8.5.2018

B23 113-100

2/2

| | |
|-------------------------------------|-------|
| Width in number of modular spacings | 4 |
| Type of interface | M-bus |
| EEC40 signature | |
| With lock code | |
| Number of positions total (counter) | 7 |
| Degree of protection (IP) | IP20 |